



IMAGE PERFORMANCE TRENDING OF THE RAPIDEYE CONSTELLATION AFTER 6 YEARS OF OPERATIONS

Andreas Brunn, Cody Anderson, Taha Moufid

Content



- RapidEye Introduction and Motivation for Quality **Trending**
- Calculation of Noise Contents
 - Fully automatic method throughout the full Image dynamic range
 - Noise trends throughout the mission lifetime
- Sensor Sensitivity Trends
- Satellite Health Trends





INTRODUCTION AND MOTIVATION FOR QUALITY TRENDING

Space Segment Overview



 Constellation of 5 small satellites equally phased in sun-synchronous orbits (approx. 630 km altitude)





Motivation



- It is normal and expected that aging of components (like camera, battery, etc.), increased by the harsh environmental conditions in space, is decreasing imaging quality and capacity
- BlackBridge wants to offer its customers always the best possible data quality => this requires a comprehensive knowledge of any image quality change
- To deliver the best quality image products to the customers the data providers need to react on changes as soon as possible



NOISE TRENDING

Detection of Homogeneous Areas




- Image area is subsetted to small blocks of adjustable size
- Blocks are polluted with poisson noise
- Pearson correlation coefficent between the polluted and un-polluted block is calculated as a measure of homogeneity
- The lower the original block is correlating to its polluted twin, the more homogeneous the block is





Homogeneous Area => Low correlation





Heterogeneous Area => Higher correlation

Detected Homogeneous Areas








Noise Evaluation



 All detected homogeneous blocks have different radiance levels

$$NOISE = \frac{Mean(DN)}{STDDEV(DN)}$$

- Noise for each of the blocks is calculated
- Poisson noise is assumed to match the noise levels over the full dynamic range of the response




Noise Trend Estimation



- Two Tile Ids having a frequent occurrence and a high dynamic range have been processed from the archive
- A total of over 400 image products (cloud free, no blackfill) from both tile Ids have been used to trend the noise behaviour of the camera over 6 years






Noise Trend Estimation



Noise trends on different brightness levels

Trendlines over 6 years show very stable performance

Some fluctuation over the year due to seasonal sun angle changes



Noise Trends Over 6 years of Operation



Very stable image performance with regard to noise

- No band shows clear losses in image performance
- All but 3 bands show clear positive noise trend
- 3 bands are stable within the methods accuracy

	Blue	Green	Red	Red-Edge	NIR
RE1	2.60	3.87	4.61	7.04	4.79
RE2	0.61	-0.69	4.03	4.07	2.67
RE3	4.24	4.01	8.22	8.28	7.47
RE4	0.98	3.57	4.06	6.67	5.65
RE5	3.35	5.52	6.45	5.59	3.54

noise measure on Jan 31, 2015 minus noise measure Feb 01,2009




SPECTRAL RESPONSE TRENDING

Response Trending - Methodology




- 26 Sites twice per month
- Over the whole mission life
- Supported by vicarious absolute calibration




Blue Band Trends - Raw Data






Green Band Trends - Raw Data






Red band Trends - Raw Data






Red-Edge Band Trends - Raw Data





NIR Band Trends - Raw Data





Raw Data Trends - Conclusion



- There are small degradation trends in the sensor response of all bands and all spacecraft.
- Such trends are expected and normal for CCD based spacecraft cameras. The measured degradations are smaller than expected.
- All of the shown trends have been corrected in the products which are fully compliant to the specifications.




SPACECRAFT HEALTH TRENDS

Info from: Dr. Kam Shahid


Technical Status - Onboard Fuel





Technical Status - Battery





Battery capacity extrapolation.
Red line marks the point where the imaging capicity has to be reduced due to power limitations.

Independent 3rd Party Assessment



- "It is clear that the RE mission operations team has demonstrated both the expertise and creativity to continue successfully maintaining and operating the RE constellation for the foreseeable future"
- "Since launch, the RE team has significantly upgraded their ground software, moved their operations center, and exchanged downlink antennas without impacting the operations or performance of the RE service"
- "Their responsive operations are evident by the efficient use of propellant and direct coordination and automation with the ESA Space Operations Center for ensuring safety of flight"

Life Expectancy



 It is our assessment that BlackBridge will be able to use the current RapidEye assets to meet its mission performance requirements and continue operating through 2020.

Pinnacle Space

 We estimate with a HIGH probability that the RapidEye mission can continue through 2020.

Conclusion



 Constellation after 6 years of operations is fully functional and will deliver the full image performance for another 5 or more operational years

BlackBridge in Action Volcan Villarrica, Chile





Images collected January 7, 2015 (left) and March 4, 2015 (right)

BlackBridge in Action Calbuco Volcano, Chile





Images collected March 4, 2015 (left) and April 24, 2015 (right)



Dr. Andreas Brunn Manager Calibration & Validation

andreas.brunn@blackbridge.com

BlackBridge:: Delivering the World

info@blackbridge.com www.blackbridge.com